



Enovation Apartment Sliding Door

Equal parts durable and inviting, Ezial's Enovation Apartment Sliding Doors showcase panoramic views, encouraging natural light and airflow, while still providing protection against the elements. Capable of withstanding fierce weather conditions with durable glass and high-quality seals, this product offers peace of mind and smooth, effortless operation.



FEATURES & BENEFITS

- Durable stile depth of 26mm – suitable for high-wind-load areas
- Smooth operation – innovative Ezi-Slide ball bearing rollers
- High-performance seals for climate insulation and noise reduction
- Compatible with a wide range of insect and security screens
- High performance glazing, fused with Ezi-Seal technology, delivers supreme insulation, acoustics and weather durability
- NATA tested and accredited enhanced water management



PRODUCT OPTIONS

- Versatile configuration options – highlights and sidelights
- Standard two, three and four panel configuration options
- Multi-stacking options – up to eight panels
- Single-direction or bi-parting openings
- Diverse rail options
- 90 degree post-less corner
- High and low profile sill options to suit geographical and architectural requirements
- Patented integrated framing
- Integrate AS1428.1 compliant flush sill options including compliant screen provisions

SPECIFICATIONS

FRAME SIZE

65mm, 101.6mm, 150mm

MAXIMUM OPENING SIZE

2800mm high x 11600mm wide

MAXIMUM PANEL SIZE

2750mm high x 1450mm wide

MAXIMUM PANEL WEIGHT

180kgs

MAXIMUM NO. OF PANELS

Up to 4 left + 4 right (8 in total)

GLAZING RANGE

5mm - 10.38mm (12.5mm pocket)
10.38mm - 15mm (18.5mm pocket)

WINDOW ENERGY RATING - TOTAL WINDOW AFRC

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf.
Single Glazing					
EZI-009-01	6.38mm Clear Laminate	5.9	0.67	0.73	0.41
EZI-009-02	6.38mm Grey Laminate	5.9	0.52	0.35	0.41
EZI-009-03	6.38mm Comfort Plus Grey	4.1	0.42	0.32	0.41
Double Glazing					
EZI-018-01	4mm Clear / 7mm Air / 4mm Clear	3.8	0.64	0.67	0.41
EZI-018-02	4mm Energy Tech / 7mm Air / 4mm Clear	3.3	0.55	0.63	0.41
EZI-018-03	4mm LightBridge Clear SO / 7mm Air / 4mm Clear	3.2	0.48	0.66	0.41

COMMON CONFIGURATIONS (VIEWED FROM OUTSIDE)

Our modular design enables many different configurations. A selection of possible configuration options is depicted here.

