





gateway – integrating your outdoor spaces indoors and allowing natural sunshine and breeze to nourish and revitalise your home. Intelligently designed to function seamlessly with Centor's state-of-the-art E2, E2i, and E3 hardware ranges our Top Rolling Bifold System offers optimum performance.



## FEATURES & BENEFITS

- Huge opening free of fixed glass panels, mullions and posts
- Smooth gliding operation
- Ezi-Seal technology for enhanced weather durability, insulation and acoustics
- Complete vertical and horizontal adjustments
- NATA tested and accredited







# ALFRESCO TOP ROLLING BIFOLD DOOR



# **PRODUCT OPTIONS**

- E2 hardware for quality features with economical spacious functionality
- E3 hardware for enhanced durability, acoustic insulation and larger door panels
- Bottomless sill for unobstructed room transition
- Single or double glazing

- Inward or outward folding configurations
- 90 degree post-less corner
- Single-direction or bi-parting openings
- Centor's retracting S2/S4 insect and blind screen options
- Dual and three-point locking systems for added security

#### WINDOW ENERGY RATING - TOTAL WINDOW AFRO

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf.
EZI-001-01	6mm Clear	6.0	0.59	0.61	0.03
EZI-001-07	6.38mm Grey Laminate	5.9	0.44	0.29	0.03
EZI-001-06	6.38mm Comfort Plus Grey	4.5	0.36	0.27	0.03

#### SPECIFICATIONS

FRAME SIZE

101.6mm

MAXIMUM OPENING SIZE

3100mm high x 16000mm wide

MAXIMUM PANFI SIZE

3000mm high x 1100mm wide E2 3000mm high x 1200mm wide E3

MAXIMUM PANEL WEIGHT

60kgs E2 115kgs E3

MAXIMIIM NO OF PANELS

Up to 8 left + 8 right (16 in total)

GLAZING RANGE

5mm - 13.5mm (16.2mm pocket)

13mm - 30mm (34.2mm pocket)

## COMMON CONFIGURATIONS (VIEWED FROM OUTSIDE)

Our modular design enables many different configurations. A selection of possible configuration options is depicted here.















